



STAGE FACTORY LINE®

SFL®



Page 197



Page 197



Page 197



Page 197



Page 197

SFL®

H EFFICIENT
PROFIght.



Page 199



Page 199



Art. No.: 156632

SFL® PAR20 G**Material:**
Aluminium**Dimensions:**
Mains cable-L: 30 cm**Included parts:**
Protective contact plug (incl.)**Accessory:**
see page 199**Recommended bulb:**
50W, 50°, 4000K, 400cd
575511

Art. No.: 156622

SFL® PAR20 P**Material:**
Aluminium**Dimensions:**
Mains cable-L: 30 cm**Included parts:**
Protective contact plug (incl.)**Accessory:**
see page 199**Recommended bulb:**
50W, 24°, 3300cd
519725

Art. No.: 156722

SFL® PAR36 ES111**Material:**
Aluminium**Dimensions:**
Mains cable-L: 100 cm**Included parts:**
Protective contact plug (incl.)**Accessory:**
see page 199**Recommended bulb:**
75W, 4000K, 2500cd
575671

Art. No.: 156602

SFL® PAR56 HV**Material:**
Aluminium**Dimensions:**
Mains cable-L: 100 cm**Included parts:**
Protective contact plug (incl.)**Accessory:**
see page 199**Recommended bulb:**
PAR56 GX16d
see below**SFL® PAR20/36/56**

230~



Article No.	Description	Colour	Voltage	Socket/ Bulb (excl.)	Wattage Bulb	Length in cm	Width in cm	Height in cm	Weight	Protection class
156632	SFL® PAR20 G	alu	230V AC	GU10/GU10	50W max.	16,6	8,2	8,2	0,3 kg	1
156622	SFL® PAR20 P	alu	230V AC	E27/PAR20	50W max.	16,6	8,2	8,2	0,3 kg	1
156722	SFL® PAR36 ES111	alu	230V AC	GU10/ES111	75W max.	22,0	16,2	16,2	0,7 kg	2
156602	SFL® PAR56 HV	alu	230V AC	GX16d/PAR56	300W max.	3,70	22,8	22,8	1,4 kg	1

**PAR56 GX16d 300W**

230~



Article No.	Description	Socket	Ø in cm	Light colour	Wattage	4000cd	3000cd	15°	30°	NSP	MFL
519740	Reflector bulb	GX16d	17,5	weiß	300W	4000cd		15°		NSP	
519741	Reflector bulb	GX16d	17,5	weiß	300W	3000cd		30°		MFL	

Attention! Effect spotlight! Not suitable for continuous operation.




HiEFFICIENT
PROFIlighT.

SFL® PAR56 T 70/150 LONG HV G12
Material:
 Aluminium

Dimensions:
 Mains cable-L: 100 cm

Accessory/Included parts:
 Protective contact plug (incl.)
 Ballast (incl.)

Note:
 Lamp is not suitable for colour foils!

Recommended bulb:
 70W
 507130, 3000K, 6600lm
 507131, 4200K, 12700lm

Recommended bulb:
 150W
 507140, 3000K, 14000lm
 507141, 4200K, 12700lm

HiEFFICIENT
PROFIlighT.

SFL® PAR56 TS 70/150 LONG HV Rx7s
Material:
 Aluminium

Dimensions:
 Mains cable-L: 100 cm

Accessory/Included parts:
 Protective contact plug (incl.)
 Conventional ballast (incl.)

Note:
 Lamp is not suitable for colour foils!

Recommended bulb:
 70W, 4200K, 6500lm
 509071


Recommended bulb:
 150W, 4200K, 12500lm
 509151

SFL® PAR56 T/TS Professional lamps for the commercial use.

230~



Article No.	Description	Voltage	Colour	Socket/ Bulb (excl.)	Wattage bulb	Length in cm	Width in cm	Height in cm	Rotation/ swivel range	Weight
156662	SFL® PAR T 70 Long HV G12	230V AC	alu	G12/HQ-T	70W	40,5	22,8	22,8	350°/180°	3,5 kg
156672	SFL® PAR T 150 Long HV G12	230V AC	alu	G12/HQ-T	150W	40,5	22,8	22,8	350°/180°	4,5 kg
156682	SFL® PAR TS 70 Long HV Rx7s	230V AC	alu	Rx7s/HQ-TS;CDM-TS	70W	40,5	22,8	22,8	350°/180°	3,5 kg
156692	SFL® PAR TS 150 Long HV Rx7s	230V AC	alu	Rx7s/HQ-TS;CDM-TS	150W	40,5	22,8	22,8	350°/180°	4,5 kg

ACCESSORY for SFL® PAR20/36/56

Shutters
 for SFL® PAR20
 L/W/H: 21,5/21,5/1 cm
 Art. No.: 156812

 for SFL® PAR36
 L/W/H: 47/47/2 cm
 Art. No.: 156822

 for SFL® PAR56
 L/W/H: 58/58/2 cm
 Art. No.: 156832

SFL® colour foils
 yellow
 green
 red
 blue
 orange
 Art. No.:
 156914
 156915
 156916
 156917
 156919

L/B: 75/50 cm

 For SFL® PAR flood lights up to max.
 500W. Not suitable for flood lights
 with HIT/HIT-TS/HQ-T bulbs!

SFL® C-hook
 for SFL® PAR20, 1 pce.
 Clamping range: 3,5 cm max.
 Art. No.: 156902

 for SFL® PAR36/56/64, 1 pce.
 Clamping range: 5 cm max.
 Art. No.: 156912